

We use the C-ADC of the ADBMS6830B to measure the cell voltages of the battery. The maximum lifetime error for voltage measurement is  $\pm 2$  mV, since the maximum voltage of the cell is 4.2 V. (Fig. 1) [1]

**Table 1. C-ADC DC Specifications**

Parameter	Symbol	Test Conditions/Comments	Min	Typ	Max	Unit
MEASUREMENT RESOLUTION				0.15		mV/bit
DIFFERENTIAL INPUT RANGE	$V_{DIF}$	$-0.1\text{ V} < (C_x \text{ to } V-) < 80\text{ V}$	-2		+5.5	V
ADC OFFSET VOLTAGE <sup>1</sup>				$\pm 0.1$		mV
ADC GAIN ERROR <sup>1</sup>				$\pm 0.01$		%
ADC UPDATE RATE			0.9	1	1.1	kHz
ADC TRANSITION NOISE				40		$\mu\text{V rms}$
LIFETIME CELL TOTAL MEASUREMENT ERROR	C-TME	$V_{DIF} \leq \pm 2.0\text{ V}$ $V_{DIF} \leq 3.3\text{ V}$ $V_{DIF} \leq 4.5\text{ V}$ $V_{DIF} \leq 5.5\text{ V}$			$\pm 1.5$ $\pm 1.8$ $\pm 2$ $\pm 3$	mV mV mV mV
INPUT LEAKAGE CURRENT		ADC off		0	$\pm 250$	nA
DIFFERENTIAL INPUT RESISTANCE	$R_{IN\_ADC}$	ADC on	1.6	2.2	3	M $\Omega$
DIFFERENTIAL INPUT RESISTANCE DURING OPEN WIRE DETECTION				1.75		k $\Omega$
ADC SAMPLING FREQUENCY	$f_s$		3.7	4.1	4.5	MHz

Figure 1: Table 1. C-ADC DC Specifications

**Table 2. S-ADC DC Specifications**

Parameter	Symbol	Test Conditions/Comments	Min	Typ	Max	Unit
MEASUREMENT RESOLUTION				1.5 <sup>1</sup>		mV/bit
INPUT RANGE	$V_{DIF\_S}$	$-0.1\text{ V} < (S_x \text{ to } V-) < 80\text{ V}$	-0.3		+5.5	V
ADC OFFSET VOLTAGE <sup>2</sup>				$\pm 0.2$		mV
ADC GAIN ERROR <sup>2</sup>				$\pm 0.03$		%
ADC UPDATE RATE			110	125	140	Hz
ADC TRANSITION NOISE				20		$\mu\text{V rms}$
S-ADC TOTAL MEASUREMENT ERROR	S-TME	$0\text{ V} \leq V_{DIF\_S} \leq 4.5\text{ V}$ $V_{DIF\_S} \leq 5.5\text{ V}$			$\pm 7$ $\pm 8$	mV mV
INPUT LEAKAGE CURRENT		ADC off, $V_{DIF\_S} = 5.5\text{ V}$		10	$\pm 300$	nA
DIFFERENTIAL INPUT RESISTANCE		ADC on	1	1.8	2.6	M $\Omega$
DIFFERENTIAL INPUT RESISTANCE DURING OPEN WIRE DETECTION				20		k $\Omega$
GAIN DURING OPEN WIRE DETECTION		No open wire fault	85	90	95	%
ADC SAMPLING FREQUENCY	$f_s$		3.7	4.1	4.5	MHz

<sup>1</sup> The S-ADC result registers are normalized to the weight of the C-ADC results, allowing the same voltage conversion function to be applied. See the register description for more details.

<sup>2</sup> The ADC specifications are guaranteed by the total measurement error specification.

Figure 2: Table 2. S-ADC DC Specifications

## Reference

[1] *Data Sheet ADBMS6830B Rev.0 page 5.* analog.com, 01.2024.